## JCPT(RT)

## **Self-Propelled Rough-Terrain Scissor Lifts**




ingli Dingli	JCPT1218RT	JCPT1418RT
S.W.L	454kg	363kg
S.W.L On Extension	136kg	136kg
Max.Occupants	4	3
A Max.Working Height	12.00m	14.30m
Max.Platform Floor Height	10.00m	12.30m
Overall Length(With/Without Outriggers)	3.84m/3.19m	3.84m/3.19m
Overall Width	1.76m	1.76m
Overall Height(Rails Up)	2.59m	2.74m
(B) Overall Height(Rails Down)	1.82m	1.97m
Platform Size(Length/Width (3)	2.88m×1.52m	2.88m×1.52m
G Platform Extension Size	1.43m	1.43m
Ground Clearance	0.24m	0.24m
(H) Wheelbase	2.29m	2.29m
Turning Radius(Inside/Outside)	2.15m/4.85m	2.15m/4.85m
Engine	Kubota D1105 18.6kW/2400rpm	Kubota D1105 18.6kW/2400rpr
Travel Speed(Stowed)	5.2km/h	5.2km/h
Travel Speed(Raised)	0.48km/h	0.48km/h
Up/Down Speed	38/46sec	45/46sec
Gradeability	40%	40%
Max.Working Slope(ANSI)	2°/3°	2°/3°
Max.Working Slope(CE)	1.5°/3°	1.5°/3°
Hydraulic Tank	71L	71L
Diesel Tank	47L	47L
Tyres	26×12-16.5	26×12-16.5
Weight(With/Without Outriggers)	4300kg/3900kg	5050kg/5050kg



- Standard acuipment
  Proportional controls
  Self-lock gate on platform
  Drivable at full height
  Foam-filled tyre
  4WD
  Automatic brakes system
  Swing-out engine tray
  Emergency lowering system
  Emergency lowering system
  Emergency lowering system
  Cylinder holding valve
  Onboard diagnostic system
  Tilt sensor with alarm
  Anti-restart engine protection
  All Motion Alarm
  Horn
  Safety brackets
  Hour meter
  Folding guardrails

- Folding guardrails
  Extended Platform
  Flashing beacon
  Hydraulic oil cooler
  Oscillating Chassis
  Forklift Pockets























Swing-out Engine Tray

Gradeability



7 DINGLI MACHINERY